

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >
Title	Cleanup texts for Physical Processing of SFH (16.3.6.3.1)
Date Submitted	2010-03-05
Source(s)	Mihyun Lee, Jiyun Seol, Hyunkyu Yu, Jaeweon Cho, mihyun.mac.lee@samsung.com Hoky Choi Samsung Electronics Co., Ltd.
Re:	IEEE 802.16-10/0011, "IEEE 802.16 Working Group Letter Ballot#31" Target topic: "IEEE P802.16m/D4, section 16.3.6.3.1".
Abstract	The contribution provides the clean up text for SFH
Purpose	To be discussed and adopted by TGm for the 802.16m/D5
Notice	<i>This document does not represent the agreed views of the IEEE 802.16 Working Group or any of its subgroups. It represents only the views of the participants listed in the "Source(s)" field above. It is offered as a basis for discussion. It is not binding on the contributor(s), who reserve(s) the right to add, amend or withdraw material contained herein.</i>
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.
Patent Policy	The contributor is familiar with the IEEE-SA Patent Policy and Procedures: < http://standards.ieee.org/guides/bylaws/sect6-7.html#6 > and < http://standards.ieee.org/guides/opman/sect6.html#6.3 >. Further information is located at < http://standards.ieee.org/board/pat/pat-material.html > and < http://standards.ieee.org/board/pat >.

Cleanup texts for Physical Processing of SFH (16.3.6.3.1)

Mihyun Lee, Jiyun Seol, Hyunkyu Yu, Jaeweon Cho, Hokyuu Choi
Samsung Electronics Co., Ltd.

1. Introduction

This contribution provides the cleanup text to physical processing for P-SFH and S-SFH.

~~Removed text~~

Added text

2. References

[1] IEEE P802.16m/D4, "P802.16m DRAFT Amendment to IEEE Standard for Local and metropolitan area networks Part 16: Air Interface for Broadband Wireless Access Systems", 2010-02-03

3. Proposed Text Changes

[Remedy: Adopt the following modification in page 439, line 1, section 16.3.6.3.1]

----- Start proposed text -----

16.3.6.3.1 Superframe Header

16.3.6.3.1.1 Primary Superframe Header

Figure 518 shows the physical processing block diagram for the P-SFH.

<Figure 518 is omitted>

The P-SFH IE shall be appended with 5 bits CRC as in CRC-5 ITU with initialization to 0b00000 and no bitwise flipping of the polynomial output. The generating polynomial is $G(x) = x^5 + x^4 + x^2 + 1$.

The resulting sequence of bits shall be encoded by the TBCC described in 16.3.11.2 with parameter $M = N_{Rep, P-SFH} K_{bufsize}$ and $K_{bufsize} = 4L$, where L is the number of information bits and $N_{Rep, P-SFH}$ is the number of repetition for effective code rate of [1/16] or 1/24.

The encoded bit sequences shall be modulated using QPSK.

The modulated symbols shall be mapped to two transmission streams using SFBC described in section 16.3.7.1.1 ~~for two antennas~~. The two streams using SFBC ~~may~~ shall be precoded and mapped to the transmit antennas ~~more than two antennas~~ described in section 16.3.7.1.2~~1~~.

Antenna specific symbols at the output of the MIMO ~~encoder~~/precoder shall be mapped to the resource elements as described in section 16.3.6.2.1.1. The mapping of data subcarriers across the resource elements is specified in 16.3.7.2.3

16.3.6.3.1.2 Secondary Superframe Header

Figure 519 shows the physical processing block diagram for the S-SFH.

<Figure 519 is omitted>

The S-SFH IE shall be appended with a 16-bit CRC, [CRC16-CCITT as defined in ITU-T recommendation X.25 is used](#).

The resulting sequence of bits shall be encoded by the TBCC described in 16.2.17.2 with parameter $M = N_{Rep,S-SFH}K_{bufsize}$ and $K_{bufsize} = 4L$, where L is the number of information bits.

The value of $N_{Rep,S-SFH}$ is indicated in P-SFH.

The encoded bit sequences shall be modulated using QPSK.

The modulated symbols shall be mapped to two transmission streams using SFBC [described in section 16.3.7.1.1](#).~~for two antennas~~. The two streams using SFBC ~~may~~ [shall](#) be precoded and mapped to [the transmit antennas](#) ~~more than two antennas~~ described in section 16.3.7.1.2~~+~~.

Antenna specific symbols at the output of the MIMO ~~encoder~~/precoder shall be mapped to the resource elements [as described in section 16.3.6.2.1.2](#). [The mapping of data subcarriers across the resource elements is specified in 16.3.7.2.3](#).

----- End proposed texts -----